



BOLTED UP 1/2" CARRIAGE BOLTS STAGG. @ 24" O.C.

BASEMENT 1271 S.F.

4" CONC. SLAB ON 6 MIL POLY VB & 4" WASHED GRAVEL FILL C.J. @ 20'-0" O.C. EACH WAY

3219

HIGH EFF. FURN & W.H. PROVIDE COMB AIR PER MFR. SPECS 15'-3" @ DRAIN

3x3 CONC. STOOFF ABV.

D.S.

HOLD DN. T.O.W. 12" BEL. TOP OF FINISH GRADE FOR POUR THRU FRAME KNEE WALL UNDER CANTILEVER

FIRST FLOOR CANTILEVER

UNEX 678 S.F.

5" CONC. SLAB ABV SLOPE 1/8" PER 12" TO O.H. DOOR C.J. @ 20'-0" O.C. EACH WAY

8" CONC. FDN WALL W/ #4'S TOP, MID & BOTTOM 16"x8" CONC. FTG.

8" CONC. FDN WALL 20"x8" CONC. FTG.

HOLD DN. T.O.W. 12" BEL. TOP OF FINISH GRADE FOR POUR THRU

HOLD DN. T.O.W. 12" BEL. TOP OF FINISH GRADE FOR POUR THRU

UNEX 25 S.F.

BATH

ROUGH IN PLUMBING & EXHAUST



SUN PLUMB



