



2x8 LEDGER THRU
BOLTED W/ 1/2" CARRIAGE
BOLTS STAGG. @ 24" O.C.

BASEMENT 1006 S.F.

4" CONC. SLAB ON 6 MIL
POLY V.B. & WASHED
GRAVEL FILL C.J. @ 20'-0"
O.C. EACH WAY

8" CONC. FDN
WALL W/ 2#4's
TOP, MID & BOTTOM
16"x8" CONC. FTG.

16'-4"
Q TO F.D.

HIGH EFF. GAS FURN. &
W.H. PROV. OUTSIDE
COMB. AIR AS PER
MFRS SPECS

FURN.

W.H.

HVAC SUPPLY
TO 2ND FLR
HVAC SUPPLY
TO 1ST FLR

W8x21

W8x8

30x30 CONC. FTG.
W/ #4'S 8" O.C. EA. WAY

3" STL. COL.
30x30 CONC. FTG.
W/ #4'S 8" O.C. EA. WAY

UNEX 400 S.F.

5" CONC. SLAB ABOV
SLOPE 1/8" PER 12"
TO O.H. DOOR C.J. @
20'-0" O.C. EACH WAY

ELECTRIC PANEL
(FIELD DET.
EXACT LOCATION)

SEMP
PUMP

GAS
METER

UNEXCAVATED 26 S.F.

4" CONC. SLAB ABOVE

HOLD DN TO 111



